

เหล็กเจียรนัยแม่พิมพ์ คาไบร์

ADVANCED
Carbide Tool Company

SA-TYPE

MADE IN U.S.A.

	Ø 3mm			Ø 6mm					
Model	SA-41	SA-43	SA-51	SA-1	SA-2	SA-3	SA-5	SA-6	SA-7
B (mm)	2	3	6	6	8	10	13	16	19
C (mm)	6.0	14	12.7	15.8	19	19	25	25	25
D (mm)	38	38	49.7	50	63	63	69	69	69
ลูกตะ									



END CUT ปลายคม

SB-TYPE

SK-TYPE

	Ø 6mm					
Model	SB-1	SB-2	SB-3	SB-5	SB-6	SB-7
B (mm)	6	8	10	13	16	19
C (mm)	15.8	19	19	25	25	25
D (mm)	50	63	63	69	69	69
ลูกตะ						

	Ø 6mm		
Model	SK-1	SK-3	SK-5
B (mm)	6	10	13
C (mm)	3	4.7	6.3
D (mm)	50	48.7	50.3
ลูกตะ			

SC-TYPE

	Ø 3mm			Ø 6mm			
Model	SC-41	SC-42	SC-51	SC-1	SC-3	SC-4	SC-5
B (mm)	3	3	6	6	10	11	13
C (mm)	11	14	12.7	15.8	19	25	25
D (mm)	38	38	50	50	63	69	69
ลูกตะ							

ขนาดและความเร็วรอบที่เหมาะสมกับงาน

Ø 3mm 48,000-64,000 RPM.

Ø 6mm 24,000-32,000 RPM.

Ø 9.5mm 13,000-18,000 RPM.

Ø 12.7mm 11,000-15,000 RPM.

www.boriphat.com

ราคานี้ยังไม่รวมภาษีมูลค่าเพิ่ม

ราคาอาจเปลี่ยนแปลงได้โดยมิต้องแจ้งล่วงหน้า

SD-TYPE

Model	SD-42	SD-1	SD-2	SD-3	SD-5
B (mm)	3	6	8	10	13
C (mm)	3	6	8	9.5	12.7
D (mm)	38	50	52	53.5	56.7
ลูกตะ					

SM-TYPE

Model	SM-42	SM-43	SM-1	SM-4	SM-5
B (mm)	3 14°	3 7°	6 22°	10 28°	13 28°
C (mm)	11	16	12.7	16	22
D (mm)	38	38	50	60	66
ลูกตะ					

SF-TYPE

Model	SF-42	SF-1	SF-3	SF-4	SF-5
B (mm)	3	6	9.5	11	13
C (mm)	12.7	16	19	25	25
D (mm)	38	50	63	69	69
ลูกตะ					

SG-TYPE

Model	SG-1	SG-2	SG-3	SG-5
B (mm)	6	8	10	13
C (mm)	16	19	19	25
D (mm)	50	63	63	69
ลูกตะ				

SL-TYPE

Model	SL-42	SL-1	SL-2	SL-3	SL-4	SL-6
B (mm)	3 8°	6	8	9.5	13	16
C (mm)	8	16	22	27	28	33
D (mm)	38	50	66	71	72	77
ลูกตะ						

SE-TYPE

Model	SE-1	SE-3	SE-5
B (mm)	6	10	13
C (mm)	9.5	16	22
D (mm)	50	60	66
ลูกตะ			

www.boriphat.com

ราคานี้ยังไม่รวมภาษีมูลค่าเพิ่ม

ราคาอาจเปลี่ยนแปลงได้โดยมิต้องแจ้งล่วงหน้า